

1. Optimization of cold pressing process parameters of chopped corn straws for fuel (Open Access)

Accession number: 20200708156839

Authors: Chen, Tianyou (1); Jia, Honglei (1, 2); Zhang, Shengwei (1); Sun, Xumin (1); Song, Yuqiu (3); Yuan, Hongfang (1)

Author affiliation: (1) School of Biological and Agricultural Engineering, Jilin University, Changchun; 130022, China; (2) Key Laboratory of Bionic Engineering, Ministry of Education, Jilin University, Changchun; 130022, China; (3) College of Engineering, Shenyang Agricultural University, Shenyang; 110866, China

Corresponding author: Yuan, Hongfang(yuanhongfang@jlu.edu.cn)

Source title: Energies

Abbreviated source title: Energies

Volume: 13

Issue: 3

Issue date: 2020

Publication year: 2020

Article number: 652

Language: English

E-ISSN: 19961073

Document type: Journal article (JA)

Publisher: MDPI AG, Postfach, Basel, CH-4005, Switzerland

Abstract: Pressed condensation is a key process before the reclamation of loose corn straws. In this study, the effects of stabilization time on the relaxation density and dimensional stability of corn straws were studied firstly, and then the stabilization time was determined to be 60 s by comprehensively considering the compression effect, energy consumption, efficiency and significance. On this basis, the effects of the water content (12%, 15%, 18%), ratio of pressure maintenance time to stabilization time (0, 0.5, 1), maximum compression stress (60.4, 120.8, 181.2 kPa) and feeding mass (2.5, 3, 3.5 kg) on the relaxation density, dimensional stability coefficient, and specific energy consumption of post-compression straw blocks were investigated by the Box-Behnken design. It was found that the water content, ratio of pressure maintenance time to stabilization time, maximum compression stress, and feeding mass all very significantly affected the relaxation density, dimensional stability coefficient and specific energy consumption. The interaction between water content and maximum compression stress significantly affected both relaxation density and specific energy consumption. The interaction between the ratio of pressure maintenance time to stabilization time and feeding mass significantly affected the dimensional stability coefficient. The factors and the indices were regressed by quadratic equations, with the coefficients of determination larger than 0.97 in all equations. The optimized process parameters were water content of 13.63%, pressure maintenance time of 22.8 s, strain maintenance time of 37.2 s, maximum compression stress of 109.58 kPa, and raw material feeding mass of 3.5 kg. Under these conditions, the relaxation density of cold-pressed straw blocks was 145.63 kg/m³, the dimensional stability coefficient was 86.89%, and specific energy consumption was 245.78 J/kg. The errors between test results and predicted results were less than 2%. The low calorific value of cold-pressed chopped corn straw blocks was 12.8 MJ/kg. Through the situational analysis method based on the internal and external competition environments and competition conditions (SWOT analysis method), the cold-pressed chopped corn straw blocks consumed the lowest forming energy consumption than other forming methods and, thus, are feasible for heating by farmers. Our findings may provide a reference for corn straw bundling, cold-press forming processes and straw bale re-compressing. © 2020 by the authors.

Number of references: 76

Main heading: Stabilization

Controlled terms: Dimensional stability - Energy utilization - Feeding - Fueling - Maintenance - Optimization

Uncontrolled terms: Competition environments - Compression effects - Corn straws - Pressure maintenance - Process parameters - Quadratic equations - Ratio of pressures - Specific energy consumption

Classification code: 525.3 Energy Utilization - 691.2 Materials Handling Methods - 913.5 Maintenance - 921.5 Optimization Techniques

Numerical data indexing: Mass 3.50e+00kg, Mass_Density 1.46e+02kg/m³, Percentage 1.20e+01%, Percentage 1.36e+01%, Percentage 1.50e+01%, Percentage 1.80e+01%, Percentage 2.00e+00%, Percentage 8.69e+01%, Pressure 1.10e+05Pa, Pressure 1.81e+05Pa, Specific_Energy 1.28e+07J/kg, Specific_Energy 2.46e+02J/kg, Time 2.28e+01s, Time 3.72e+01s

DOI: 10.3390/en13030652

Funding Details: Number: 2018YFD0701102, Acronym: -, Sponsor: National Basic Research Program of China (973 Program); Number: 20180101090JC, Acronym: -, Sponsor: -; Number: 51705191, Acronym: NSFC, Sponsor: National Natural Science Foundation of China;

Funding text: Funding: The authors gratefully acknowledge the financial support from the National Natural Science Foundation of China (Grant No.: 51705191), the National Key Research and Development Program of China (Grant No.: 2018YFD0701102) and Science and Nature Foundation of Jilin province (Grant No.: 20180101090JC).

Compendex references: YES

Database: Compendex

Compilation and indexing terms, Copyright 2020 Elsevier Inc.

Data Provider: Engineering Village